



**FORMIKO**  
HYDRAULICS

ROTATOR **FHR 16FD1**



**160**  
kN



**-130**  
kN



**80**  
kN

**-65**  
kN

**3400**  
nm

**71**  
kg

**40**  
l/min

Hydraulic rotator FHR 16FD1 designed for heavy duty machinery to meet the highest demands for quality and reliability. Ideal for intensive professional use in forestry, agriculture, road and building construction, recycling industry, general cargo and material handling.






Rotator's upper mount is applied in FORK form factor of the knuckle joint. Robust and tough built to withstand even overloads. The fork width (between fork ends) is common standard width 100mm and the knuckle pin diameter 45mm.



FHL 03

Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws



For additional information relating to price levels and technical data, please contact [sales@formiko.lv](mailto:sales@formiko.lv)

#### Formiko Hydraulics Ltd

Dzircema Str. 119 k-1,  
Rīga LV1055 LATVIA

+371 294 49 552  
+371 264 59 383  
[sales@formiko.lv](mailto:sales@formiko.lv)  
[www.formiko.lv](http://www.formiko.lv)

On request by special conditions there are metric nipples available for rotator FHR 16FD1



FORESTRY



GENERAL CARGO



AGRICULTURE



CONSTRUCTION



RECYCLING



Current document is automatic generated at [www.formiko.lv](http://www.formiko.lv) on 03/27/2020.  
Please always make sure that it's up to date and try to be paperless!



Hydraulic rotator FHR 16FD1 designed for heavy duty machinery to meet the highest demands for quality and reliability. Ideal for intensive professional use in forestry, agriculture, road and building construction, recycling industry, general cargo and material handling.



Rotator's upper mount is applied in FORK form factor of the knuckle joint. Robust and tough built to withstand even overloads. The fork width (between fork ends) is common standard width 100mm and the knuckle pin diameter 45mm.



Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws



Rotator FHR 16FD1 based on reliable vane type hydraulic motor which delivers torque up to 3400Nm at 25MPa.



Formiko Hydraulics rotator FHR 16FD1 is equipped with double bearings to withstand both tensional and pushing loads.



Some parts in rotator are built from shock resistant and deformation resistant forged steel.



Formiko rotator FHR 16FD1 is compatible with FHL 03 series links.



Rotator for shipping is packed in compact solid cardboard box with dimensions 450x250x250mm.



We providing TWO year warranty for this rotator.

For additional information relating to price levels and technical data, please contact [sales@formiko.lv](mailto:sales@formiko.lv)

**Formiko Hydraulics Ltd**

Dzirčiema Str. 119 k-1,  
Rīga LV1055 LATVIA

+371 294 49 552

+371 264 59 383

[sales@formiko.lv](mailto:sales@formiko.lv)

[www.formiko.lv](http://www.formiko.lv)

On request by special conditions there are metric nipples  
available for rotator FHR 16FD1



FORESTRY



GENERAL CARGO



AGRICULTURE



CONSTRUCTION



RECYCLING

